

Eiki 3279A

Cassette Recorder /Player

KEY FEATURES

Record level led indicator Automatic level control 3-digit, 2X tape counter Built-in Electret microphone Auxiliary Input jack (3.5mm) Remote Mic. Jack (3.5mm) Remote pause jack (2.46mm)



OPTIONAL ACCESSORIES

Standard headset Remote control microphone 3279A

Specifications

Туре	Portable AC/battery recorder player	Signal To Noise Ratio	40dB
Frequency Response	125Hz to 8 KHz	Audio: Output	Speakers 100mm (4") round x 1
Wow & Flutter	0.30%	Speaker Jacks	1/4", 4 Ohm x 1
Battery or AC Operation	AC/DC (6"C")	Dimensions (H x W x D)	2.75" x 11.5" x 7.125
Remote Microphone Jack	1/8" (3.5mm x 1)	Weight	4 lbs.
Auxilary Input Jack	1/8" (3.5mm x 1)	Packaged Weight	2,49 kg without batteries
Remote Pause	1/10" (2.46 mm) x 1	Power Requirements	AC 120 Volts, 60Hz, DC 12 Volts (6 "C" size batteries)
Headset Jacks	1⁄4" x 4		(0 0 3120 batteries)
Audio Output:	Amplifier 1 Watts RMS (D.H.T. 5%)	Power Consumption	10 W approximately
		Safety Compliance	UL Listed
		Warranty - Unit	1-Year limited warranty from date of original purchase for parts and labour.

Specifications subject to change without notice. ©2002 Eiki International, Inc. Issued June 12, 2001.